

The power behind competitiveness

# Delta UPS – Agilon Family

VX Series, Line-interactive  
600/1000VA

## Reliable power protection for small business and home office applications

The Agilon VX line-interactive UPS designed with microprocessor control offers reliable and cost-effective power protection for PCs, laptops, POS, and other sensitive electronics used in home offices and small businesses. The integrated Automatic Voltage Regulation (AVR) ensures all electronics are receiving stable power while providing higher availability. The Agilon VX series' LED indicators, auto-shutdown software and other superior features make these units perfect for your data protection.

### Reliability

- The integrated AVR (Automatic Voltage Regulation) stabilizes the output voltage for better power quality
- Excellent microprocessor control enables accurate detection of power frequency for higher reliability
- Wide input voltage range allows the UPS to work in harsh electrical environments and reduces battery discharging time
- Batteries are automatically recharged even when the UPS is in off mode and the UPS can start without mains (Cold-Start)
- UPS is able to restart automatically while utility power is recovering
- Surge protection defends your critical load against damage



### Convenience

- Several standard Indian sockets simplify the connectivity to computer and IT peripherals
- Compact size saves more space for critical equipment

### Manageability

- Standard USB communication port enhances monitoring and manageability (Only applicable for 1000VA model)
- Advanced UPS management software provides remote shutdown and control



PC



Monitor



ADSL



Home



POS



# Delta UPS – Agilon Family

VX Series, Line-interactive  
600/1000VA

Technical Specifications			
Model		VX-600VA	VX-1000VA
Part No.		UPA601V2100B0	UPA102V2100B0
Power Rating		600VA/360W	1000VA/600W
Input	Nominal Voltage	230 Vac	
	Voltage Range	140 ~ 300 Vac (full load)	
	Nominal Frequency	50/60 Hz	
Output	Voltage	230 Vac ± 10% (Battery mode)	
	Frequency Range	50/60 Hz ± 1 Hz	
	Waveform (Batt. Mode)	Simulated Sinewave	
	Receptacle	India Socket x 3	India Socket x 4
Battery	Battery Type & Number	12V/7 Ah x 1	12V/7 Ah x 2
	Recharge Time	4 ~ 6 hours to 90%	
	Cold Start	Yes	
Indicator		LED	
Communication	Standard	N/A	USB Port x 1
Interfaces			
Environment	Operating Temperature	0 ~ 40°C	
	Altitude	0 ~ 1000m	
	Relative Humidity	0 ~ 90% (non-condensing)	
Audible Noise		< 40 dB	
Conformance	Safety	BIS	
Physical	Dimensions (W x D x H)	101 x 279 x 142 mm	130 x 320 x 182 mm
	Net Weight	4.2 kg	7.8 kg

All specifications are subject to change without prior notice.



600VA rear view



1000VA rear view



Delta offers a full range of UPS solutions from 600 VA to 4000 kVA to fulfill your power security needs.

## **COSTA POWER INDUSTRIES PVT. LTD.**

209, 2nd Floor, Infinity Business Park, Behind Pendharkar College,  
MIDC Phase – 1, Dombivli(E), Thane – 421023.  
Phone No. - 9820710392 / 9372217661.  
Email - sales@upsbatteriesindia.com / sunil@upsbatteriesindia.com.



2007~ 2008 Forbes Asia's  
Fabulous 50



2009 Frost & Sullivan  
Green Excellence Award for  
Corporate Leadership



ISO 9001:2015



ISO 14001:2015



OHSAS 18001:2007



ISO 14064-1:2012

